

2

NAVSWC TR 91-76

OTIC
JUL 13 1991

AD-A238 899



A FUZZY NEURAL MODEL FOR TARGET RECOGNITION

**BY KIRAN R. BHUTANI ALI FARSAIE BRENDA DAY
WEAPONS SYSTEMS DEPARTMENT**

4 FEBRUARY 1991

Approved for public release; distribution is unlimited.



NAVAL SURFACE WARFARE CENTER

Dahlgren, Virginia 22448-5000 • Silver Spring, Maryland 20903-5000

91-06008




A FUZZY NEURAL MODEL FOR TARGET RECOGNITION

**BY KIRAN R. BHUTANI ALI FARSAIE BRENDA DAY
WEAPONS SYSTEMS DEPARTMENT**

4 FEBRUARY 1991

Approved for public release; distribution is unlimited.



NAVAL SURFACE WARFARE CENTER
Dahlgren, Virginia 22448-5000 • Silver Spring, Maryland 20903-5000


FOREWORD

The last decade has witnessed tremendous interest and development in artificial neural networks. They are beginning to be accepted as powerful adaptive tools for solving a variety of recognition problems. Despite their dynamic success, there is a perpetual challenge presented by the human brain, which can handle tasks dealing with fuzzy or uncertain data. In this report, we demonstrate that merging of neural networks and fuzzy sets, where the former is a powerful tool for performing massive computation and the latter for coping with uncertainty, provides better tools for modeling the human classification process.

This study was partially funded by the Office of Naval Technology (ONT). Kiran R. Bhutani, currently with The Catholic University of America, was an ONT Postdoctoral Fellow at the Naval Surface Warfare Center while this study was carried out.

This technical report was reviewed by Dr. Kenneth F. Caudle, Head of the Advanced Weapons Division.

Approved by:



KURT F. MUELLER
Deputy Department Head
Weapon Systems Department

CONTENTS

	<u>Page</u>
INTRODUCTION	1
DESCRIPTION OF THE MODEL	3
ARCHITECTURE	3
TRAINING PROCESS	7
CLASSIFICATION PROCESS	8
CONCLUSION	10
REFERENCES	11
DISTRIBUTION	(1)

ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
1	STRUCTURE OF THE MODEL	5

INTRODUCTION

Defense capabilities, which are being sought by the Navy, require effective weapon systems. Major improvements in autonomous real-time target recognition are critically needed to achieve success with the next generation of smart weapons. Neural networks have attracted tremendous interest in the last decade. They are beginning to be accepted as powerful adaptive tools for manipulating and solving a variety of problems related to target recognition, speech recognition, stock market prediction, etc.

Artificial neural networks are modelled based on the biological nervous system and inspired essentially by the neurosciences and computer sciences fields. These networks provide a greater degree of robustness and fault tolerance than sequential computers. Thus the decision making process of the network is not globally affected due to a local damage of few nodes. The human brain on the other hand is capable of handling and performing tasks dealing with fuzzy or uncertain data. Indeed the majority of us think fuzzy in most situations, and much of human reasoning is imprecise in nature. Thus human reasoning is not suitable for formalization within the language of classical logic and probability theory.

Fuzzy set theory as pioneered by L. A. Zadeh¹ and investigated further by many researchers^{2,3} provides tools for

modeling uncertainty and ambiguity which is so prevalent in human interpretation and thought process. This promising field, which is a generalization of abstract set theory, allows us to assign a degree of membership to an object for a class. This degree is a number between "0" and "1", where "0" means no membership and "1" means full membership. For the classification task, the human mind evaluates the perceived information by assigning memberships to the various attributes in the input space and the stored classes.

Thus in order to build intelligent systems for target recognition, we must understand and represent mathematically the issue of uncertainty in human knowledge. We believe that the merging of neural nets and fuzzy sets, where the former is a powerful tool for performing massive computations and the later for coping with uncertainty, will provide better tools for emulating human classification process.

This paper reports development of a preliminary neural net model which can be viewed as a dynamical network. It is aimed to incorporate fuzziness into the network, thus resulting in improved performance of the recognition process.

DESCRIPTION OF THE MODEL

ARCHITECTURE

The proposed model is a dynamical neural net model with the number of levels, as well as the number of neurons in the input layer of each level, to be determined by the user. Each level of the network has an input layer, two hidden layers, and an output layer (see Figure 1). The number of neurons in the first hidden layer at each level is equal to the number of neurons in the input layer. This number is equal to the number of features input at that level. The number of neurons in the second hidden layer at each level is equal to the number of targets, and the number of neurons in the output layer is equal to the number of target classes plus 1, an extra node for no match.

Assume there are n levels in the network and k targets with m features of each target input to the system. Let m_1, m_2, \dots, m_n be the number of features input to the various levels $1, 2, \dots, n$ then $m_1 + m_2 + \dots + m_n = m$. We denote the i -th feature of the j -th target by f_{ij} , and the tolerance associated with the i -th feature of the j -th target by Q_{ij} . We associate a vector $(f_{i1}, f_{i2}, \dots, f_{ik})$ representing the i -th features of the various targets with the i -th neuron in the first hidden layer. We also associate a vector $(Q_{1j}, Q_{2j}, \dots, Q_{tj})$ representing the tolerance vector associated with the target

j , with the j -th neuron in the second hidden layer at any level, where t is the number of features input at that level.

Every level k (except level 1) in the network receives input from level $(k-1)$ as well as a new set of features of the target. The justification of having various levels in the network rests essentially on the fact that the human mental processing scheme goes through various levels of classification for identifying an object. We first look at the strongest features of an object and try to classify based on that information. However if the decision can't be made at the strongest level (that is, at level 1 in the proposed network), we then go to the next set of features and try to classify with the help of additional information. This process continues until all the features at our disposal have been consumed. If the first level of the network can classify the target, there is no need to proceed to the other levels. However if no classification is made at the first level, computation is carried out sequentially at the next level and so on until the classification decision is made.

From the i -th neuron in the first hidden layer (representing the i -th features) to the j -th neuron in the second hidden layer (representing the j -th target), we have a vector denoted by $W_{ij} = (w_{i1j}, w_{i2j}, \dots, w_{imj})$, where w_{inj} represents some relation between the i -th and the n -th feature of the j -th target with the i -th and the n -th feature of the input vector.

Let $a = (a_1, a_2, \dots, a_n)$ be the input vector consisting of





FIGURE 1. STRUCTURE OF THE MODEL

features of unknown target which has to be classified. The computation at each neuron in hidden layer 1 is carried out as follows. Consider the neuron representing the first feature of each target.

Compute $|f_{11} - a_1|, |f_{12} - a_1|, \dots, |f_{1m} - a_1|$; then

$$k = \min_{1 \leq j \leq m} \{|f_{1j} - a_1|\}$$



At each neuron in hidden layer 1, the network selects the class or classes (k) which minimize the distance between the stored feature and the input feature. We consider these classes winners at that neuron. Among these winners we select those targets which have a maximum number of wins. These are our winners at hidden layer 1, and they are the possible candidates for classification of the unknown feature vector. The neurons corresponding to these target winners become active in hidden layer 2. Assume target 1 and target 2 are winners at hidden layer 1, that is, they have the maximum number of matches with the input feature vector. Computations from hidden layer 1 to hidden layer 2 are carried for

neurons representing these targets. Let $C_1 = (c_{11}, c_{21}, \dots, c_{n1})$ be the feature coefficients of target 1 which are fixed. The output at neuron 1 (corresponding to target 1) in hidden layer 2 is represented by

$$(P_{11}, P_{21}, \dots, P_{n1}) = \sum_{i=1}^n \phi_i(a_i, w_{i1})$$

where ϕ is some nonlinear function of the input vector and the weights. This vector $\bar{P}_1 = (P_{11}, P_{21}, \dots, P_{n1})$ is then compared with the tolerance at that vector denoted by $\bar{Q}_1 = (Q_{11}, Q_{21}, \dots, Q_{n1})$, and the degree of match between the unknown input vector \bar{a} and the target class 1 is obtained by the method described in classification.

TRAINING PROCESS

Let (a_1, a_2, \dots, a_n) be the features of the first target. We then require that the output at the first neuron $\bar{P}_1 = (P_{11}, P_{21}, \dots, P_{n1})$ in hidden layer 2, at level 1 be less than or equal to the tolerance vector $\bar{Q}_1 = (Q_{11}, Q_{21}, \dots, Q_{n1})$ associated with that neuron. Assume for some k that $P_{k1} \geq Q_{k1}$. Then the point P_1 lies outside the hyper-rectangle* $h(Q_1)$ in the n -dimensional space with the longest diagonal from the origin to the point Q_1 . We say the

*If one considers two features of target 1, then $\bar{Q}_1 = (Q_{11}, Q_{21})$ and so the hyper-rectangle $h(Q_1)$ in this case is obtained by drawing a rectangle in the plane with one vertex at the origin and the opposite vertex at the point (Q_{11}, Q_{21}) .

closest point to P_1 in the hyper-rectangle is a point $T_1 = (T_{11}, T_{21}, \dots, T_{n1})$, where

$$T_{k1} = \begin{cases} P_{k1} & \text{if } P_{k1} \leq Q_{k1} \\ Q_{k1} & \text{if } P_{k1} \geq Q_{k1} \end{cases}$$

Training requires that we change the weights and tolerances in such a way that $h(Q_1)$ expands and $T_1 = P_1$, that is, P_1 falls in the hyper-rectangle $h(Q_1)$. We interpret the training of the network as creating weak or co-weak isomorphism⁴ of itself until it reaches a stable state, a state when $T_1 = P_1$.

CLASSIFICATION PROCESS

For the purpose of classification, we apply fuzzy reasoning to assign a degree of membership between unknown input features and the target classes.

Assume target class k is the winner at hidden layer 1 and let $(P_{1k}, P_{2k}, \dots, P_{nk})$ be the output of neuron representing target class k in hidden layer 2. Recall that at this neuron a vector $(Q_{1k}, Q_{2k}, \dots, Q_{nk})$ is associated. This vector represents tolerance the features of target k input at level 1. Let

$$m_{jk} = (Q_{jk} - P_{jk}) c_{jk}$$

where c_{jk} is the j -th feature coefficient of the k -th target and is

fixed. We define the degree of membership m_k of the input vector and target class k to be

$$\begin{aligned} m_k &= 1 - \sum_{j=1}^n (Q_{jk} - P_{jk}) c_{jk} \\ &= 1 - \sum_{j=1}^n m_{jk} \end{aligned}$$

where n is the number of features input at level 1. The above formula of assigning class memberships considers to a greater degree those features whose weights are high. If the j -th feature coefficient c_{jk} is high, then larger difference $(Q_{jk} - P_{jk})$ would contribute to a large number for m_k and thus to a small degree of membership m_k in the target class k . If c_{jk} is low, then m_{jk} is low regardless of whether input features match the features of the k -th target strongly or not. The feature coefficients c_{jk} indicate the extent to which the j -th feature of the k -th target is important for classification purposes. The c_{jk} which are the degree of importance of the features will be computed using statistical methods. The winning target is the one for which the degree of membership is the highest, that is, target k is the winner if

$$m_k = \max_{1 \leq i \leq L} (m_i)$$

where L is the number of targets.

CONCLUSION

A mathematical model of a multi-level, multi-layer neural net was developed which uses fuzzy theory for classification. The developed architecture would allow imprecise or incomplete knowledge gained at one level of the network to be forwarded as additional input to the next level of the network. Fuzzy theory allows us to interpret the information in a more general form for developing methods in pattern clustering and recognition. For the model under development, a number of issues still need to be investigated. Some of these are:

1. Application of fuzzy theory in structuring neural networks for handling uncertain and imprecise concepts.
2. Mathematical representation of flow of information dealing with ambiguity from one level to the next level of the network.

REFERENCES

1. Zadeh, L. A., "Fuzzy Sets," Information and Control, Vol. 8, 1965, pp. 338-353.
2. Kosko, B., "Fuzzy Entropy and Conditioning," Information Sciences, Vol. 40, 1986, pp. 165-174.
3. Kandel, A., Fuzzy Techniques in Pattern Recognition, John Wiley & Sons, Inc., New York, NY, 1982.
4. Bhutani, K. R., "On Automorphisms of Fuzzy Graphs," Pattern Recognition Letters, Vol. 9, 1989, pp. 159-162.

DISTRIBUTION

	<u>Copies</u>		<u>Copies</u>
Office of the Chief of		H	1
Naval Research		J	1
Office of Naval Technology		K	1
Attn: ONR Code 1133	1	K10	1
ONR Code 12	1	K40	1
ONT Code 20T	1	K44 (L. Reid)	1
ONT Code 21	1	K50	1
ONT Code 22	1	N	1
ONT Code 23	1	N30	1
800 No. Quincy Street		N40	1
Arlington, VA 22217-5000		N41 (R. McClintock)	1
		R	1
Defense Technical		R04	1
Information Center		R05	1
Cameron Station		R40	1
Alexandria, VA 22304-6145	12	R44	1
		U	1
Library of Congress		U04	1
Attn: Gift and Exchange		U20	1
Division	4	U30	1
Washington, DC 20540			
Internal Distribution:			
C	1		
D	1		
D2	1		
D4	1		
E	1		
E231	2		
E232	3		
F	1		
G	1		
G06	1		
G07	1		
G10	1		
G20	1		
G30	1		
G40	1		
G42	1		
G42 (Farsaie)	2		
G42 (Dumoulin)	2		

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 4 February 1991	3. REPORT TYPE AND DATES COVERED Interim Report	
4. TITLE AND SUBTITLE A Fuzzy Neural Model for Target Recognition			5. FUNDING NUMBERS	
6. AUTHOR(S) Kiran R. Bhutani, Ali Farsaie, and Brenda Day				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Surface Warfare Center White Oak Laboratory (Code G42) 10901 New Hampshire Avenue Silver Spring, MD 20903-5000			8. PERFORMING ORGANIZATION REPORT NUMBER NAVSWC TR 91-76	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) A mathematical model of a multi-level, multi-layer neural network was developed which uses fuzzy theory for classification. This model would allow imprecise or incomplete knowledge gained at one level of the network to be forwarded as additional input to the next level of the network. Fuzzy theory allows us to interpret the information in a more general form for developing methods in pattern clustering and recognition. We believe this approach will incorporate human thinking and decision making into neural networks.				
14. SUBJECT TERMS neural networks pattern recognition fuzzy theory clustering feature coefficients degree of membership			15. NUMBER OF PAGES 19	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT SAR	

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and its title page. Instructions for filling in each block of the form follow. It is important to **stay within the lines** to meet **optical scanning requirements**.

Block 1. Agency Use Only (Leave blank).

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

BLOCK 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (If Known)

Block 11. Supplementary Notes. Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement.

Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."
DOE - See authorities.
NASA - See Handbook NHB 2200.2
NTIS - Leave blank.

Block 12b. Distribution Code.

DOD - Leave blank.
DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.
NASA - Leave blank.
NTIS - Leave blank.

Block 13. Abstract. Include a brief (**Maximum 200 words**) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (**NTIS only**)

Blocks 17.-19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.